



The **air curtain** adopts cross flow blower to generate **high speed air flow** downward, that be installed upward side of the entrance door or window, to isolate the indoor air from the outdoor air and **reduce the loss of indoor cool air**, also **prevent the insects and dust** from entering the indoor environment.

AIR CURTAIN

TERMINAL

『VENTILATION』

Air Curtain



Quiet function



Compact design



Multi fan speed



Easier maintainability



- > **Air Flue Design**—optimized air flue design can greatly improve the fan efficiency and lower the operation noise.
- > **Flexible Installation**—flexible air inlet/outlet directions, meet different installation requirements.
- > **Washable Filter**—washable filter is optional when equipped with air return box.
- > **Wide Application**—usable for both 50/60Hz.

- **Gree Air Curtains** are a simple but durable solution for professional needs.
- They come in two models, **90 and 120 cm** wide with a symmetrical centered fan motor, allowing the combination of units to suit the required dimension.
- The models are made of galvanized steel frame, equipped with a two speed reliable motor, allowing for both low noise and high air flow volume up to 1.650 m³/h.

Model		FM-1.25-9K	FM-1.25-12K
Power Supply	V/Hz	220-230/50	220-230/50
Power Input	W	110	140
Airflow Volume	m ³ /h	1200	1650
Sound Pressure Level	dB(A)(H/L)	59/56	61/56
Outline Dimension (WxDxH)	mm	900x215x193	1200x215x193
Package Dimension	mm	1015x270x256	1315x270x256
Net Weight/Gross Weight	kg	16/18	20/22
Setting Height	m	2.3 - 3	2.3 - 3

*NOTE: For The Improvement, The Specifications, Designs and Information In This Catalogue Are Subjected To Change Without Prior Notice.