



▶ **R32 Eco-Friendly Refrigerant**  
No damage to ozone layer;  
Higher heating exchange efficiency

# T-FRESH

NON-INVERTER SERIES

**1**  
YEAR  
WARRANTY FOR  
SPARE PARTS

**3**  
YEARS  
WARRANTY FOR  
COMPRESSOR



FLOOR STANDING


▶ Simple Design Brings Life To Its Original Nature



Beautiful Integrated Design



Precise Air Guiding



Concealed Display Screen and Touch Control Button



▶ 9.1 Side-drawing filter design for convenient cleaning

The filter adopts user-friendly side-drawing design, which is more convenient for cleaning



Floor Standing  
**T-FRESH**  
NON-INVERTER SERIES



Timer



Lock



Quick Cooling



Closed Structure of Connection Pipe Outlet



Refrigerant Lacking Protection



Intelligent & Controllable Electric Heating



Quiet Design



Wide Operation Climate Range



Healthy Filters



Auto Restart



Intelligent Defrosting Monitor



LED Display

| Model                     |              | GVC24AL-K6NNC7A          |                        | GVC48AL-M6NNC7A          |                           |           |
|---------------------------|--------------|--------------------------|------------------------|--------------------------|---------------------------|-----------|
| Cooling Capacity          |              | kW                       | 7.00                   |                          | 12.31                     |           |
|                           |              | Btu/h                    | 23,884                 |                          | 42,000                    |           |
| COP                       |              | W/W                      | 2.80                   |                          | 2.80                      |           |
| EER                       |              | Btu/h/W                  | 9.55                   |                          | 9.55                      |           |
| Power Supply              |              | Ph,V,Hz                  | 1Ph, 220-240V, 50Hz    |                          | 3Ph, 380-415V, 50Hz       |           |
| Power Input               | Cooling      | W                        | 2500                   |                          | 4390                      |           |
| Rated Current             | Cooling      | A                        | 18.00                  |                          | 9.55                      |           |
| Refrigerant Charge Volume |              | kg / oz                  | 1.62 / 49.4            |                          | 2.30 / 81.1               |           |
| <b>Indoor Unit</b>        |              | <b>GVC24AL-M6NNC7A/I</b> |                        | <b>GVC48AL-M6NNC7A/I</b> |                           |           |
| Airflow Volume            |              | m <sup>3</sup> /h        | 1000 / 800 / 710 / 600 |                          | 1900 / 1850 / 1700 / 1530 |           |
|                           |              | CFM                      | 547 / 471 / 418 / 353  |                          | 1118 / 1089 / 1000 / 900  |           |
| Sound Pressure Level      | Indoor       | dB(A)(SH/H/M/L)          | 46 / 44 / 41 / 38      |                          | 53 / 50 / 48 / 45         |           |
| Outline Dimension         | WxHxD        | mm                       | 507 x 1770 x 320       |                          | 587 x 1882 x 394          |           |
| Weight/Gross Weight       | Indoor       | kg                       | 38.5/52                |                          | 55/77.5                   |           |
| <b>Outdoor Unit</b>       |              | <b>GVC24AL-M6NNC7A/O</b> |                        | <b>GVC48AL-M6NNC7A/O</b> |                           |           |
| Sound Pressure Level      | Outdoor      | dB(A)                    | 57                     |                          | 59                        |           |
| Outline Dimension         | WxHxD        | mm                       | 963 x 700 x 396        |                          | 1032 x 1250 x 412         |           |
| Weight/Gross Weight       | Outdoor      | kg                       | 60/64.5                |                          | 107/118                   |           |
| Connection Pipe           | Gas          | mm / inch                | 12.70 / 1/2"           |                          | 15.88 / 5/8"              |           |
|                           | Liquid       | mm / inch                | 6.35 / 1/4"            |                          | 9.52 / 3/8"               |           |
|                           | Max Distance | Height                   | m / ft                 | 20 / 65.6                |                           | 20 / 65.6 |
|                           |              | Length                   | m / ft                 | 25 / 82.0                |                           | 30 / 98.4 |
|                           | Length       | m / ft                   | 7.5 / 24.6             |                          | 7.5 / 24.6                |           |
| Gas Additional Charge     |              | g/m                      | 12.00                  |                          | 12.00                     |           |
|                           |              | oz/ft                    | 0.129                  |                          | 0.129                     |           |
| Refrigerant               |              |                          | R32                    |                          | R32                       |           |

\*NOTE: For The Improvement, The Specifications, Designs and Information In This Catalogue Are Subjected To Change Without Prior Notice.